

Product Information

JB GERMAN OIL Super ZH - M

J1151



Description

JB GERMAN OIL Super ZH - M is a special hydraulic oil on the basis of synthetic oils with high-quality additives. Thanks to its special formulation, the properties of JB GERMAN OIL Super ZH - M play a crucial role. We guarantee an excellent cold stability. JB GERMAN OIL Super ZH - M has a high performance as a central hydraulic oil in power steering, rear axle for hydrostatic drive of ventilators, alternators and air conditioning systems, for stability and traction systems (ABS/ASR/ASC), central locking, electro-hydraulic convertible top controls, hydraulic brake boosters and hydropneumatic suspension for VW, Audi, Seat and Skoda. Especially for use in cold countries.

Instructions for use

JB GERMAN OIL Super ZH - M is designed for use from -60°C to +130°C and is therefore recommended for the latest developments on the automotive market.

Quality classification

Specification

- DIN 51524-2
- ISO 7308

Recommendation

- Land Rover Cold Climate PAS Fluid 14315
- Peugeot/Citroën 9979 A1
- MB 343.0
- SAAB 93 160 548
- Opel 1940 766
- VOLVO 30741424
- PSA B71 2710
- VW G 004 000

Properties

- Reliable protection against corrosion
- Extremely low pour point
- Improved viscosity and friction behavior
- A very good wear protection
- An excellent thermal stability
- A good foaming behavior
- Neutral towards sealing agents

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	25,3	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,1	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	267		DIN ISO 2909:2004-08
Appearance	GREEN FLOURESCENT		VISUELL
Density at 15°C	840	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-66	°C	ASTM D 7346:2015