

Product Information

JB GERMAN OIL Farmer Super SAE 30 Mineral 4 Takt | j2033



Description

JB GERMAN OIL Farmer Super SAE 30 Mineral 4 Takt is a mono-grade engine-oil. Selected base oils and additives ensure optimum lubrication and operational safety.

Instructions for use

JB GERMAN OIL Farmer Super SAE 30 Mineral 4 Takt is suitable for 4-stroke mowing machines. The operating instructions of the engine manufacturer must be observed.

Quality classification

Specifications

- API SG/CF
- ACEA E2/B4

Properties

- Suitable for catalysts
- Very good shear stability
- Prevention of the formation of black mud
- High oxidation stability
- Stable and excellent viscosity behavior
- Good detergents and dispersing properties
- Neutrality against sealing materials
- Great protection against wear and corrosion

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	11,8	mm ² /s	DIN ISO 51562-2
viscosity index	100		DIN ISO 2909
appearance	YELLOW		visuell
density at 15°C	882	kg/m ³	DIN EN ISO 12185
pour point	-27	°C	ASTM D 7346

JB GERMAN OIL GmbH & Co. KG · Wörlzower Weg 13-19 · D-19243 Wittenburg · Telefon +49 38852 90620 · Telefax +49 38852 906220

Note: All listed information complied with the latest knowledge and developments at the time of preparation. Our products will be continuously developed. For this reason, our products, manufacturing processes and all related information on this product page may change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under corresponding laboratory conditions and are to be regarded as general, non-binding guideline values.

Last Update: March 12, 2021