## **Product Information**

## JB GERMAN OIL Agrar Super TC-W II RED

875

-27

J2034



DIN EN ISO 12185:1997-11

ASTM D 7346:2015

## Description

JB GERMAN OIL Agrar Super TC-W II RED is a premixed, mineral oil-based lubricant for 2-stroke engines. It reduces carbon deposits in the piston ring grooves, the combustion eviction and the outlet ports. JB GERMAN OIL Agrar Super TC-W II RED reduces rust damage in the engine parts and the dirtying of spark plugs.

## Instructions for use

Density at 15°C

Pour Point

JB GERMAN OIL Agrar Super TC-W II RED is recommended for the lubrication of air and water cooled 2-stroke petrol engines such as lawn mowers, motorcycles, mopeds, scooters, chain saws etc. It is suitable for the lubrication of separate lubricating systems or self-mixing systems. Recommended mixing ratio: 1:50 (oil : fuel). Observe manufacturer's instructions.

Quality classification			
Specification			
• API TC		• JASO FB	
• ISO-L-EGB			
Properties			
• Excellent corrosion protection		Reduction of coking	
Excellent oxidation stability		Environmentally friendly with low smoke emissions	
Very good wear protection			
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	66,6	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9,0	mm²/s	DIN 51659-2:2017-02
Viscosity Index	110		DIN ISO 2909:2004-08
Appearance	RED		VISUELL

kg/m³

°C

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.