# **Product Information**

## JB GERMAN OIL Super Cross Grand Prix

J2059



#### Description

JB GERMAN OIL Super Cross Grand Prix is a synthetic 2-stroke oil based on synthetic base oils, selected 2-stroke additives and a PIB component. It is characterised by its high wear protection and reduced corrosion, as well as a prevention of deposits and glow-ignitions. JB GERMAN OIL Super Cross Grand Prix is ideally suited to air and watercooled 2-stroke engines, as well as for separate-lubrication and self-mixing systems.

### Instructions for use

JB GERMAN OIL Super Cross Grand Prix is recommended for the lubrication of air-cooled 2-stroke petrol engines with a very high speed and the heaviest loads, as well as for the lubrication of separate-lubrication and self-mixing systems. JB GERMAN OIL Super Cross Grand Prix is suitable for high-quality, high speed units such as brush cutters, leaf vacuums, Chainsaw and so on, with over 6,000 rpm.

Quality classification		
Specification		
• API TC	• ISO-L-EGD	
• JASO FD		
Recommendation		
• Husqvarna	• Rotax	
• Piaggio Hexagon	• Stihl	
Properties		
High cleaning performance	<ul> <li>Free of combustion residue and deposits to the greatest</li> </ul>	
Possible extent	<ul> <li>Clean spark plugs provide for an optimum performance of the engine</li> </ul>	
<ul> <li>Excellent lubrication of all engine parts</li> </ul>	<ul> <li>Low exhaust fumes due to high combustion rate</li> </ul>	
<ul> <li>High wear and corrosion protection</li> </ul>		

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	68,0	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	10,6	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	144		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Density at 15°C	868	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-39	°C	ASTM D 7346:2015	

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.