according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6

Page 1/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

Article No.:

i2061...

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Lubricant

* 1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

JB German Oil GmbH

Wölzower Weg 13 - 19 19243 Wittenburg

Germany

Telephone: +49 (0) 38852 90620 Telefax: +49 (0) 38852 906220 E-mail: Vertrieb@jb-germanoil.de Website: www.jb-germanoil.de

E-mail (competent person): vertrieb@jb-germanoil.de

* 1.4. Emergency telephone number

Abt. Produktsicherheit, 24h: +49 228 192 40 (Informationszentrale gegen Vergiftungen Bonn), +49 (0) 38852 90620 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

According to EC directives or the corresponding national regulations the product does not have to be labelled.

Hazard statements: none

Supplemental hazard information: none

Precautionary statements: none

2.3. Other hazards

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6

Page 2/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	0 - ≤ 1.32
EC No.: 265-169-7	Asp. Tox. 1 (H304)	weight-%
REACH No.: 01-2119471299-27	♦ Danger	
	Acute Toxicity Estimate	
	ATE (oral) > 5,000 mg/kg	
	ATE (dermal) > 2,000 mg/kg	
	ATE (inhalation, dust/mist) > 5 mg/L	

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

* 4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. Consult a doctor immediately.

In case of skin contact:

Consult a doctor immediately.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

Rinse mouth thoroughly with water. Consult a doctor immediately. Rinse mouth. Get medical advice/ attention if you feel unwell. Let 1 glass of water be drunken in little sips (dilution effect).

Self-protection of the first aider:

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Observe risk of aspiration if vomiting occurs.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Use water spray jet to protect personnel and to cool endangered containers. Water spray jet alcohol resistant foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

During heating or in case of fire, toxic gases is possible.

The formation of combustible vapours is possible at temperatures above: Flash point Combustible

Hazardous combustion products:

Carbon monoxide, Carbon dioxide (CO2), Nitrogen oxides (NOx),

During heating or in case of fire, toxic gases is possible. In case of fire: Gases/vapours, toxic

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6 Page 3/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Special danger of slipping by leaking/spilling product. Avoid breathing dust/fume/gas/mist/vapours/spray. Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

Emergency procedures:

Remove persons to safety.

6.1.2. For emergency responders

Personal protection equipment:

Use personal protection equipment. Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Suitable material for taking up: Sand, Kieselguhr, Universal binder, Chemical binding agents, containing acids Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Remove from the water surface (e.g. skimming, sucking). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information:

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

6.5. Additional information

Clear spills immediately. Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Personal protection equipment: see section 8 When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Clear spills immediately. Use appropriate container to avoid environmental contamination. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

No special fire protection measures are necessary. Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6 Page 4/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

Environmental precautions:

See section 8.

Advices on general occupational hygiene

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Suitable container/equipment material: Floors should be impervious, resistant to liquids and easy to clean. Shafts and sewers must be protected from entry of the product.

Keep/Store only in original container.

Hints on storage assembly:

not required

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Store in a cool dry place. Keep away from heat.

7.3. Specific end use(s)

Recommendation:

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

No data available

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Phosphorodithioic acid, mixed O, Obis (2-ethylhexyl and isobutyl) esters, zinc salts CAS No.: 68442-22-8 EC No.: 270-478-5	8.05 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
Phosphorodithioic acid, mixed O, Obis (2-ethylhexyl and isobutyl) esters, zinc salts CAS No.: 68442-22-8 EC No.: 270-478-5	11.4 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
calcium carbonate CAS No.: 471-34-1 EC No.: 207-439-9	6.36 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	4.37 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	1.09 mg/m ³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.62 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects

en / DE

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

Substance name	DNEL value	① DNEL type
		② Exposure route
Benzenamine, N-phenyl-, reaction	0.31 mg/kg	-
products with 2,4,4-trimethylpentene		① DNEL Consumer
CAS No.: 68411-46-1 EC No.: 270-128-1	, , , ,	② Long-term - dermal, systemic effects
Benzenamine, N-phenyl-, reaction	0.31 mg/kg	① DNEL Consumer
products with 2,4,4-trimethylpentene	bw/day	② Long-term - oral, systemic effects
CAS No.: 68411-46-1 EC No.: 270-128-1		
Isomer mixture of C7-9-alkyl-3- (3,5-	2.33 mg/m ³	① DNEL worker
di-trans-butyl-4-hydroxyphenyl)		② Long-term – inhalation, systemic effects
propionate CAS No.: 125643-61-0		
EC No.: 406-040-9		
Substance name	PNEC Value	① PNEC type
Distillates (petroleum), solvent-	9.33 mg/kg	① PNEC secondary poisoning
refined heavy paraffinic CAS No.: 64741-88-4		
EC No.: 265-090-8		
Distillates (petroleum), solvent-	9.33 mg/kg	① PNEC secondary poisoning
dewaxed heavy paraffinic		
CAS No.: 64742-65-0 EC No.: 265-169-7		
Phosphorodithioic acid, mixed O, O-	4 μg/L	① PNEC aquatic, freshwater
bis (2-ethylhexyl and isobutyl) esters,		The aquate, hestimates
zinc salts		
CAS No.: 68442-22-8 EC No.: 270-478-5		
Phosphorodithioic acid, mixed O, O-	4.6 μg/L	① PNEC aquatic, marine water
bis (2-ethylhexyl and isobutyl) esters,		
zinc salts CAS No.: 68442-22-8		
EC No.: 270-478-5		
Phosphorodithioic acid, mixed O, O-	100 mg/L	① PNEC sewage treatment plant
bis (2-ethylhexyl and isobutyl) esters,		
zinc salts CAS No.: 68442-22-8		
EC No.: 270-478-5		
Phosphorodithioic acid, mixed O, O-	0.04508 mg/	① PNEC sediment, freshwater
bis (2-ethylhexyl and isobutyl) esters, zinc salts	kg	
CAS No.: 68442-22-8		
EC No.: 270-478-5		
Phosphorodithioic acid, mixed O, O-	0.00451 mg/	① PNEC sediment, marine water
bis (2-ethylhexyl and isobutyl) esters, zinc salts	kg	
CAS No.: 68442-22-8		
EC No.: 270-478-5		
Phosphorodithioic acid, mixed O, O- bis (2-ethylhexyl and isobutyl) esters,	0.00676 mg/	① PNEC soil
zinc salts	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
CAS No.: 68442-22-8		
EC No.: 270-478-5		
Phosphorodithioic acid, mixed O, O- bis (2-ethylhexyl and isobutyl) esters,	10.67 mg/kg	① PNEC secondary poisoning
zinc salts		
CAS No.: 68442-22-8		
EC No.: 270-478-5		

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6 Page 6/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

Substance name	PNEC Value	① PNEC type
Phosphorodithioic acid, mixed O, Obis (2-ethylhexyl and isobutyl) esters, zinc salts CAS No.: 68442-22-8 EC No.: 270-478-5	45 μg/L	① PNEC aquatic, intermittent release
calcium carbonate CAS No.: 471-34-1 EC No.: 207-439-9	100 mg/L	① PNEC sewage treatment plant
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.0338 mg/L	① PNEC aquatic, freshwater
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.0038 mg/L	① PNEC aquatic, marine water
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	10 mg/L	① PNEC sewage treatment plant
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.446 mg/kg	① PNEC sediment, freshwater
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.0446 mg/kg	① PNEC sediment, marine water
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	2.59 mg/kg	① PNEC soil

* 8.2. Exposure controls

8.2.1. Appropriate engineering controls

See section 7. No additional measures necessary.

8.2.2. Personal protection equipment

Eye/face protection:

During transfer: Eye glasses with side protection

Wear eye/face protection. EN 166

Skin protection:

Hand protection

Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), CR (polychloroprene, chloroprene rubber)

Thickness of the glove material: ≥ 0,4 mm

Breakthrough time: 480 min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Tested protective gloves must be worn: EN ISO 374

Suitable protective clothing: Protective clothing In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Usually no personal respirative protection necessary.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6
Page 7/11

JB GERMANOIL DAS MOTOROIL

JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

8.2.3. Environmental exposure controls

See section 7. No additional measures necessary.

8.3. Additional information

Mineral oil mist limits:

OSHA PEL - value 5 mg / m³, ACGIH STEL - value of 10 mg / m³

SECTION 9: Physical and chemical properties

lack 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: tawny

Odour: not determined

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	No data available		
Flash point	232 °C		
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Vapour density	No data available		
Density	854 kg/m³	15 °C	
Bulk density	not applicable		
Water solubility	No data available		
Dynamic viscosity	No data available		
Kinematic viscosity	73 mm²/s	40 °C	
Pou Point	-42 °C		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions. Combustible

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

To avoid thermal decomposition do not overheat.

10.5. Incompatible materials

Materials to avoid: Acid, Oxidising agent, Reducing agent

10.6. Hazardous decomposition products

Hazardous combustion products: Carbon dioxide, Carbon monoxide, Nitrogen oxides (NOx) Gases/vapours, toxic

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6

Page 8/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Distillates (petroleum), solvent-dewaxed heavy paraffinic CAS No.: 64742-65-0 EC No.: 265-169-7

LD₅₀ oral: >5,000 mg/kg

LD₅₀ dermal: >2,000 mg/kg

LC₅₀ Acute inhalation toxicity (dust/mist): >5 mg/L

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

* 12.1. Toxicity

Distillates (petroleum), solvent-dewaxed heavy paraffinic CAS No.: 64742-65-0 EC No.: 265-169-7

LC₅₀: >1,000 mg/L 4 d (fish, Salmo gairdneri)

EC₅₀: >1,000 mg/L 2 d (crustaceans, Daphnia Magna)

EC₅₀: >1,000 mg/L 4 d (Algae/water plant, Scenedesmus subspicatus)

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6

Do mo 0/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

* 12.5. Results of PBT and vPvB assessment

Distillates (petroleum), solvent-dewaxed heavy paraffinic CAS No.: 64742-65-0 EC No.: 265-169-7

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

13.2. Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land two secut (ADD/DID	\ Imlandatamusaus#	Con tunnement (IMDC)	Air turn non-out (ICAO TI
Land transport (ADR/RID	(ADN)	Sea transport (IMDG)	Air transport (ICAO-TI /
14.1. UN number or	ID number		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.2. UN proper shi	pping name		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport haz	ard class(es)		
not relevant	not relevant	not relevant	not relevant
14.4. Packing group)	•	
not relevant	not relevant	not relevant	not relevant
14.5. Environmenta	l hazards		
not relevant	not relevant	not relevant	not relevant
14.6. Special preca	utions for user		
not relevant	not relevant	not relevant	not relevant
	•	-	•

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

This product is not assigned to a hazard category.

Safety data sheet available for professional user on request.

en / DE

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6

Page 10/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

15.1.2. National regulations

[DE] National regulations

Störfallverordnung (12. BlmschV)

for substances contained in the product:

This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

To follow: 5.2.5 Water hazard class

WGK:

1 - slightly hazardous to water

Source:

Self-classification (mixture: calculation rule).

Technische Regeln für Gefahrstoffe

TRGS 510

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Berufsgenossenschaftliche Informationen (DGUV-Informationen) 868

Berufsgenossenschaftliche Regeln (DGUV-Regeln) 189, 190, 192, 195

Other regulations, restrictions and prohibition regulations

Altöl-Verordnung (AltölV)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
1.4.	Emergency telephone number
2.2.	Label elements
3.2.	Mixtures
4.1.	Description of first aid measures
8.1.	Control parameters
8.2.	Exposure controls
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.5.	Results of PBT and vPvB assessment
14.3.	Transport hazard class(es)
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes
16.2.	Abbreviations and acronyms
16.5.	List of relevant hazard statements and/or precautionary statements from sections 2 to 15

16.2. Abbreviations and acronyms

American Conference of Governmental Industrial Hygienists
European Agreement concerning the International Carriage of Dangerous Goods by Inland
Waterways
European Agreement concerning the International Carriage of Dangerous Goods by Road
Chemical Abstracts Service
Classification, Labelling and Packaging
derived no-effect level
Effective Concentration 50%
International Civil Aviation Organization
International Maritime Dangerous Goods

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Jul 2024 Print date: 29 Jul 2024

Version: 6 Page 11/11



JB GERMAN OIL Truckstar (UHPD) HC-LA SAE 5W-30

IMO International Maritime Organization

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health OSHA Occupational Safety & Health Administration PBT persistent and bioaccumulative and toxic

PEL Permissible Exposure Limit
PNEC Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals

RID Dangerous goods regulations for transport by rail

STEL Short-term Exposure Limit

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds See overview table at www.euphrac.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data

EC 1907/2006 - REACH Regulation

 $1272/2008\ EC$ - Regulation on classification, labeling and packaging of substances and mixtures, and amending Directives 67/548/EEC and 1999/45/EC and Regulation (EC) No 1907/2006

Regulation (EC) No 1907/2006 (REACH), Annex II

European Chemicals Agency (ECHA), C & L classification and labeling inventory

European Chemicals Agency (ECHA), ECHA CHEM Registered substances

OECD The Global Portal to Information on Chemical Substances (ChemPortal)

May be fatal if swallowed and enters airways.

Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA): GESTIS substance database and International limit values for chemical substances

Federal Environment Agency, Section IV 2.4: Documentation and Information Centre substances hazardous to water Rigoletto (catalog substances hazardous to water)

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

* 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements

16.6. Training advice

No data available

H304

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version.