

Product Information

JB GERMAN OIL Longlife DXS GM 5W-30

J2064



Description

JB GERMAN OIL Longlife DXS GM 5W-30 is a fully synthetic Mid SAPS smooth-running engine oil for petrol car engines with or without turbocharging and direct injection. JB GERMAN OIL Longlife DXS GM 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

JB GERMAN OIL Longlife DXS GM 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol car engines. According to dexos1™ Gen3 specification it is recommended for General Motors under all operating conditions. The operating instructions of the car and engine manufacturers must be observed.

Quality classification

Specification

- API SN Plus (RC)
- ILSAC GF-5/GF-6A
- API SP (RC)

Recommendation

- Chrysler MS-6395
- dexos1™ Gen3
- Fiat 9.55535-CR1
- Ford WSS-M2C929-A, Ford WSS-M2C946-A/-B1
- Ford WSS-M2C961-A
- GM 6094M
- Opel/Vauxhall OV0401547-G30
- VWC 53034

Properties

- A very stable and excellent viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Excellent protection against wear, corrosion and foaming
- High oxidation stability
- Excellent cold starting properties
- Fuel savings under all operating conditions
- Neutrality towards sealants
- Suitable for catalytic converters
- A secure lubricant film at very high operating temperatures

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	60,1	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	10,8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	172		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -30°C	4100	mPa*s	ASTM D 5293:2020
Density at 15°C	846	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015
Total Base Number (TBN)	7,1	mgKOH/g	ASTM D 2896:2015