

Product Information

JB GERMAN OIL Super Spezial Synt 0W-16

J2074



Description

JB GERMAN OIL Super Spezial Synt 0W-16 is a synthetic smooth-running engine oil for petrol car engines with or without turbocharging and direct injection. JB GERMAN OIL Super Spezial Synt 0W-16 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

JB GERMAN OIL Super Spezial Synt 0W-16 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol car engines. It therefore reduces the CO2 emissions and contributes to the protection of the environment. JB GERMAN OIL Super Spezial Synt 0W-16 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SP
- ILSAC GF-5/GF-6B

Recommendation

- Honda 08215-99974, Honda 08216-99974
- Honda 08232-P99S1LHE, Honda Ultra Next/Ultra Green
- Hybrid Engine Nissan KLANM-01A04 Extra Save X Eco
- Mitsubishi Diaqueen ECO Plus
- Mitsubishi MZ102661, Mitsubishi MZ102662
- Toyota 08880-11005

Properties

- Fuel savings under all operating conditions
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Extended oil change intervals protect natural re-sources
- Excellent cold starting properties, even at low temperatures
- A very stable and excellent viscosity behaviour and shear stability
- Very good detergent and dispersing properties
- Excellent protection against wear, corrosion and foaming

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	39,1	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,3	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	154		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -35°C	4410	mPa*s	ASTM D 5293:2020
Density at 15°C	842	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-66	°C	ASTM D 7346:2015
Total Base Number (TBN)	8,1	mgKOH/g	ASTM D 2896:2015