

# Product Information

## JB GERMAN OIL Lightrun 2000S SAE 10W-40 | j2082



### Description

**JB GERMAN OIL Lightrun 2000S SAE 10W-40** is a high-quality smooth-running engine oil for year-round use in highly stressed aspirated and turbo diesel engines as well as petrol engines. It has an excellent flow behaviour, even at low temperatures. It quickly reaches critical lubrication points, thus ensuring a considerable reduction in wear during the warm-up phase. Selected active ingredients ensure maximum engine cleanliness, even in short-haul traffic. **JB GERMAN OIL Lightrun 2000S SAE 10W-40** allows for extended oil change intervals in accordance with manufacturer's instructions, and high wear protection with low oil and fuel consumption.

### Instructions for use

**JB GERMAN OIL Lightrun 2000S SAE 10W-40** is ideal for mixed fleets and can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

### Quality classification

#### Specifications

- API CI-4/SL
- ACEA A3/B4
- ACEA E3/E5/E7
- Global DHD-1
- JASO DH-1

#### Recommendation

- Allison C-4
- Caterpillar ECF-2 / TO-2
- Cummins CES 20076/20077/20078
- DAF
- DDC 93K215
- Deutz DQC III-10
- Mack EO-N
- MAN M 3275-1
- MB 228.3 / 229.1 / 235.28
- MTU Type 2
- Renault VI RLD-2
- Voith Retarder B
- Volvo VDS-3
- VW 500 00/501 01/505 00

### Properties

- Very good detergent and dispersing properties
- High resistance to oxidation and ageing
- Protection against reflective surface formation
- Good cold starting properties
- Extended oil change intervals protect natural resources

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	98,8	mm <sup>2</sup> /s	DIN ISO 51562-2
kinematic viscosity at 100°C	14,5	mm <sup>2</sup> /s	DIN ISO 51562-2
viscosity index	152		DIN ISO 2909
appearance	BROWN		visuell
density at 15°C	869	kg/m <sup>3</sup>	DIN EN ISO 12185
pour point	-36	°C	ASTM D 7346

JB GERMAN OIL GmbH & Co. KG · Wörlzower Weg 13-19 · D-19243 Wittenburg · Telefon +49 38852 90620 · Telefax +49 38852 906220

Note: All listed information complied with the latest knowledge and developments at the time of preparation. Our products will be continuously developed. For this reason, our products, manufacturing processes and all related information on this product page may change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under corresponding laboratory conditions and are to be regarded as general, non-binding guideline values.