

Product Information

JB GERMAN OIL Super F1 RS Power SAE 5W-40

J2086



Description

JB GERMAN OIL Super F1 RS Power SAE 5W-40 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. With JB GERMAN OIL Super F1 RS Power SAE 5W-40, a reliable and heavy-duty engine oil has been developed to guarantee the low viscosity of SAE 5W-class as well as a low evaporation loss. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

JB GERMAN OIL Super F1 RS Power SAE 5W-40 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. JB GERMAN OIL Super F1 RS Power SAE 5W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SP/CF
- ACEA A3/B4

Recommendation

- BMW Longlife-98
- Porsche A40 ab Modelljahr 1973 (außer Cayenne V6)
- Fiat 9.55535-H2/-M2/-N2
- PSA B71 2296
- MB 229.3
- Renault RN0700/RN0710
- Opel GM LL-B-025
- VW 502 00/505 00

Properties

- Fuel savings under all operating conditions
- Excellent cold starting properties, even at low temperatures below -30°C
- Very good detergent and dispersing properties
- A very stable and excellent viscosity behavior and shear stability
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources
- Low evaporation, thus low oil consumption

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	93.1	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	15.4	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	176		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -30°C	5960	mPa*s	ASTM D 5293:2020
Density at 15°C	853	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015
Total Base Number (TBN)	9.8	mgKOH/g	ASTM D 2896:2015