

Product Information

JB GERMAN OIL Hydrauliköl HLP 46

J2245



Description

JB GERMAN OIL Hydrauliköl HLP 46 is an optimally alloyed hydraulic oil. It has a high level of performance and a wide range of applications within the entire industry. JB GERMAN OIL Hydrauliköl HLP 46 is characterized especially by a very good viscosity and temperature behavior, high resistance to aging and reliable corrosion protection.

Instructions for use

JB GERMAN OIL Hydrauliköl HLP 46 is suitable for all hydraulic systems and universally applicable. The use of JB GERMAN OIL Hydrauliköl HLP 46 is recommended especially for use in circulation systems, for the supply of small gearboxes, for thermally highly stressed hydraulic systems with high-pressure pumps of all models, in sensitive control systems, and for hydraulic systems in agriculture.

Quality classification

Specification

- AFNOR NF E 48-603 HM
- ASTM D6158
- CETOP RP 91H HM
- DIN 51524-2
- GB 111118.1 L-HM (conventional)
- ISO 11158 HM
- ISO 6743-4 HM
- JCMAS HK
- MIL-PRF-17672 E
- NATO H-573
- SAE MS1004 HM
- SEB 181 222
- US Steel 126/127/136
- VDMA 24318

Recommendation

- Arburg
- Atos
- Bosch Rexroth RE-90220
- Danieli Hydraulics
- Denison HF-0/HF-1/HF-2
- Eaton/Sperry Vickers I-286-S
- Eaton/Sperry Vickers M-2950-S
- Fives Cincinnati P-55/P-70
- GM LH-02-1-04, GM LS-2
- Metso
- Müller Weingarten
- Sauer-Danfoss 520L0463
- ZF TE-ML 07H

Properties

- High level of performance
- High resistance to aging
- Excellent wear protection
- Very good viscosity and temperature behavior
- Reliable corrosion protection, neutral towards sealants

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	46,1	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,2	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	116		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	864	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015