

Product Information

JB GERMAN OIL ATF DQ 5000 (Red) | j2272



Description

JB GERMAN OIL ATF DQ 5000 (Red) is an automatic gear oil on a basis of the latest technology of HC/HT hydrocrack oils, which is permitted by General Motors for use in vehicles with automatic gearboxes. The special formulation ensures a lifespan that is twice as long as that of a comparable ATF oil. **JB GERMAN OIL ATF DQ 5000 (Red)** meets the requirements of the gear oil specifications of General Motors for all vehicles with hydramatic automatic gearboxes from 2006 onwards.

Instructions for use

JB GERMAN OIL ATF DQ 5000 (Red) is fully backward compatible with DEXRON®-III (H), III and IIE applications. Always follow the recommendations in your vehicle's instruction manual.

Quality classification

Specifications

- GM DEXRON®-VI
- Aisin Warner AW-1
- Aisin Warner JWS 3324

Recommendation

- ATF Type 3.0, ATF Type 3.1
- BMW/Mini ATF 3+
- Ford/Lincoln/Mercury XT-6-DSP [SP]
- Ford/Lincoln/Mercury XT-6-QSP [SP]
- Honda ATF DW-1
- Hyundai/Kia NWS 9638 T-5
- Jaguar/Land Rover Fluid 8432
- Mazda FZ, Mazda FW 6A EL, Mazda FW 6AX EL
- MB 236.12, MB 236.14, MB 236.41
- Mitsubishi ATF-J3, Mitsubishi Diaqueen ATF-PA
- Nissan Matic-S
- Porsche 000 043 304 00
- Shell 3353/134/M-1375.4/12108
- SP-IV/SPH-IV/SP-IV-RR
- Toyota Scion FZ, Toyota WS (JWS 3324)
- VW G 052 533, VW G 055 005 A/A2
- VW G 055 540 A2, VW G 060 162 A1/A2/A6
- ZF Lifeguardfluid 5/6

Properties

- Very good lubricating capacity even at low temperatures in the winter
- High, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against wear, corrosion and foaming
- An excellent friction value stability
- High thermal and oxidative stability
- An excellent cooling capacity
- Excellent shear stability
- Minimum evaporation losses
- Neutral behavior against sealing materials
- Neutral behavior through inhibition compared to non-ferrous metals

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	29,1	mm ² /s	DIN ISO 51562-2
kinematic viscosity at 100°C	6,0	mm ² /s	DIN ISO 51562-2
viscosity index	161		DIN ISO 2909
appearance	RED		visuell
density at 15°C	841,0	kg/m ³	DIN EN ISO 12185
pour point	-48	°C	ASTM D 7346

JB GERMAN OIL GmbH & Co. KG · Wölzower Weg 13-19 · D-19243 Wittenburg · Telefon +49 38852 90620 · Telefax +49 38852 906220

Note: All listed information complied with the latest knowledge and developments at the time of preparation. Our products will be continuously developed. For this reason, our products, manufacturing processes and all related information on this product page may change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under corresponding laboratory conditions and are to be regarded as general, non-binding guideline values.

Last Update: March 11, 2021