

Product Information

JB GERMAN OIL Longlife WIV 1 Plus SAE 5W-30 | j2419



Description

JB GERMAN OIL Longlife WIV 1 Plus SAE 5W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Minimization of friction, wear and fuel consumption, excellent cold starting properties. Extended oil change intervals as per manufacturer's instructions. **JB GERMAN OIL Longlife WIV 1 Plus SAE 5W-30** extends the lifetime of the diesel particulate filter by means of a reduced concentration of ash-forming particles in the exhaust gas. Reduces the release of harmful emissions into the environment. Offers increased safety due to continuously high protection of the engines. It achieves a high viscosity index thanks to its formulation with special base oils.

Instructions for use

JB GERMAN OIL Longlife WIV 1 Plus SAE 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for use in modern petrol and diesel engines. **JB GERMAN OIL Longlife WIV 1 Plus SAE 5W-30** is suitable for extended oil change intervals and extends the lifespan of the particulate filter. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Approvals

- VW 504 00/507 00

Specifications

- API SN
- ACEA C3

Recommendation

- BMW Longlife-04
- Fiat 9.55535-S3
- MB 229.31, MB 229.51
- Porsche C30

Properties

- Excellent cold starting properties, even at low temperatures below -25°C
- A very stable and excellent viscosity behavior and shear stability
- Fuel savings under all operating conditions
- Secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	69,8	mm ² /s	DIN ISO 51562-2
kinematic viscosity at 100°C	12,1	mm ² /s	DIN ISO 51562-2
viscosity index	172		DIN ISO 2909
appearance	YELLOWBROWN		visuell
density at 15°C	850	kg/m ³	DIN EN ISO 12185
pour point	-45	°C	ASTM D 7346

JB GERMAN OIL GmbH & Co. KG · Wöhlzower Weg 13-19 · D-19243 Wittenburg · Telefon +49 38852 90620 · Telefax +49 38852 906220

Note: All listed information complied with the latest knowledge and developments at the time of preparation. Our products will be continuously developed. For this reason, our products, manufacturing processes and all related information on this product page may change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under corresponding laboratory conditions and are to be regarded as general, non-binding guideline values.