

Product Information

JB GERMAN OIL Outboard Oil Hightec Speed

J2650



Description

JB GERMAN OIL Outboard Oil Hightec Speed is a synthetic 2-stroke oil based on synthetic base oils, selected 2-stroke additives and a PIB component. It is characterised by its high wear protection and reduced corrosion, as well as a prevention of deposits and glow-ignitions. JB GERMAN OIL Outboard Oil Hightec Speed is ideally suited to air and watercooled 2-stroke engines, as well as for separate-lubrication and self-mixing systems.

Instructions for use

JB GERMAN OIL Outboard Oil Hightec Speed is recommended for the lubrication of air-cooled 2-stroke petrol engines with a very high speed and the heaviest loads, as well as for the lubrication of separate-lubrication and self-mixing systems. JB GERMAN OIL Outboard Oil Hightec Speed is suitable for high-quality, high speed units such as brush cutters, leaf vacuums, Chainsaw and so on, with over 6,000 rpm.

Quality classification	
Specification	

- | | |
|--|---|
| <ul style="list-style-type: none">• API TC• JASO FD | <ul style="list-style-type: none">• ISO-L-EGD |
|--|---|

Recommendation	
<ul style="list-style-type: none">• Husqvarna• Piaggio Hexagon	<ul style="list-style-type: none">• Rotax• Stihl

Properties	
<ul style="list-style-type: none">• High cleaning performance• Possible extent• Excellent lubrication of all engine parts• High wear and corrosion protection	<ul style="list-style-type: none">• Free of combustion residue and deposits to the greatest• Clean spark plugs provide for an optimum performance of the engine• Low exhaust fumes due to high combustion rate

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	68,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	10,6	mm²/s	DIN 51659-2:2017-02
Viscosity Index	144		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	868	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015