

Product Information

JB GERMAN OIL ATF III G RED

J2268



Description

JB GERMAN OIL ATF III G RED is designed on a basis of hydrocrack oils and PAO with special additives and inhibition. JB GERMAN OIL ATF III G RED was developed especially for the indicated specifications and purposes. It provides Maximum lubrication and wear protection thanks to its special additives. JB GERMAN OIL ATF III G RED is a universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic gearboxes with and without regulated converter lockup clutch (so-called gear-clutch lock-up), for which gear fluids of type Dexron III H are required.

Instructions for use

JB GERMAN OIL ATF III G RED is especially suitable for use in gearboxes with ATF Dexron III G specifications. JB GERMAN OIL ATF III G RED is miscible with all brands of ATFs. It is recommended to flush with JB GERMAN OIL ATF III G RED first, before the final filling with JB GERMAN OIL ATF III G RED is performed. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- GM Dexron® III G
- Ford MERCON®

Recommendation

- DTFR 13C100 (236.1), MB 236.5
- VOITH H55.6335.XX (G607)
- Ford WSA-M2C195-A
- ZF TE-ML 02F/03D/04D/09/11B/14A/17C
- MAN 339 Typ Z-1/V-1

Properties

- Reliable protection against wear, corrosion and foaming
- High and very stable viscosity index
- Problem-free at very low temperatures
- Very low pour point
- Very good oxidation stability
- Well coordinated friction properties
- Neutral towards sealing agents
- Neutral behavior towards non-ferrous metals due to inhibition

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	35,0	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,2	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	176		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	848	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-54	°C	ASTM D 7346:2015