

Product Information

JB GERMAN OIL ATF DQ 3000 (Red) | j2270



Description

JB GERMAN OIL ATF DQ 3000 (Red) is designed on a basis of hydrocrack oils and PAO with special additives and inhibition. **JB GERMAN OIL ATF DQ 3000 (Red)** was developed especially for the indicated specifications and purposes. It provides maximum lubrication and wear protection thanks to its special additives. **JB GERMAN OIL ATF DQ 3000 (Red)** is a universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic gear-boxes with and without regulated converter lockup clutch (so-called gear-clutch lock-up), for which gear fluids of type Dexron III H are required.

Instructions for use

JB GERMAN OIL ATF DQ 3000 (Red) is especially suitable for use in gear-boxes with ATF Dexron III H specifications. **JB GERMAN OIL ATF DQ 3000 (Red)** is miscible with all brands of ATFs. It is recommended to flush with AVENO Dexron III H first, before the final filling with **JB GERMAN OIL ATF DQ 3000 (Red)** is performed. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specifications

- GM Dexron® III H

Recommendation

- Allison C-4, Allison TES-389
- BMW 83 22 9 407 807, BMW 83 22 9 407 858
- Caterpillar TO-2
- Ford Mercon, M2C138-CJ, 166-H
- MB 236.1, MB 236.2, MB 236.6, MB 236.7, MB 236.9, MB 236.10
- MAN 339 Typ L1/V1/V2/Z1/Z2
- VOITH H 55.6336.3x Extended Drain (G1363), 55.6335
- VOLVO 1161521, VOLVO 1161511, VOLVO 97340, VOLVO 97341
- VW G 052 162 (TL 521 62)
- ZF TE-ML 02F/03D/04D/09A/09B/11B/14A/17C

Properties

- Reliable protection against wear, corrosion and foaming
- High and very stable viscosity index
- Problem-free at very low temperatures
- Very low pour point
- Very good oxidation stability
- Well coordinated friction properties
- Neutral towards sealing agents
- Neutral behavior towards non-ferrous metals due to inhibition

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	7,2	mm ² /s	DIN ISO 51562-2
viscosity index	176		DIN ISO 2909
appearance	RED		visuell
density at 15°C	852	kg/m ³	DIN EN ISO 12185
pour point	-54	°C	ASTM D 7346

JB GERMAN OIL GmbH & Co. KG · Wöhlzower Weg 13-19 · D-19243 Wittenburg · Telefon +49 38852 90620 · Telefax +49 38852 906220

Note: All listed information complied with the latest knowledge and developments at the time of preparation. Our products will be continuously developed. For this reason, our products, manufacturing processes and all related information on this product page may change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under corresponding laboratory conditions and are to be regarded as general, non-binding guideline values.

Last Update: March 11, 2021