

Product Information

JB GERMAN OIL ATF CVT | j2274



Description

JB GERMAN OIL ATF CVT is a latest generation automatic gearbox lubricant for CVT automatic gearboxes. **JB GERMAN OIL ATF CVT** guarantees optimum power transmission. **JB GERMAN OIL ATF CVT** is designed on a basis of synthetic oils with special additives and inhibition, which guarantee the flawless function of the automatic gearbox.

Instructions for use

JB GERMAN OIL ATF CVT was developed for use in CVT automatic gearboxes (belt CVT and chain CVT). **JB GERMAN OIL ATF CVT** ensures a stable viscosity, even under the highest mechanical stresses in the transmission elements (push belt). *Use in Honda CVT (HMMF) with starting clutch is not recommended.

Quality classification

Recommendation

- Audi G 052 180, Audi G 052 516
- BMW/Mini EZL 799
- Chrysler/Dodge/Jeep CVTF+4
- Chrysler/Dodge/Jeep NS-2
- Daihatsu TC, Daihatsu Amix CVTF-DC/CVTF-DFE
- Ford CVT23/30, Ford MERCON® C
- GM/Saturn DEX-CVT
- Honda HCF-2, Honda HMMF
- Hyundai/Kia CVTF
- MB 236.20
- Mitsubishi CVTF-Diaqueen J-1/J-4
- Mitsubishi Diaqueen NS-2
- Nissan NS-2/NS-3
- Renault ELFMATIC
- Subaru NS-2/ECVT/iCVT, Subaru Lineartronic CVTF
- Suzuki TC/NS-2, Suzuki CVT Fluid Green 1/Green 2
- Toyota TC

Properties

- Very good lubrication properties, even at low temperatures in winter
- Very high and stable viscosity index
- Very low pour point
- Very good oxidation stability
- Most extensive protection against wear, corrosion and foaming
- Well coordinated friction properties
- Neutral behavior towards sealing agents
- Neutral behavior towards non-ferrous metals due to inhibition

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	32,6	mm ² /s	DIN ISO 51562-2
kinematic viscosity at 100°C	7,1	mm ² /s	DIN ISO 51562-2
viscosity index	190		DIN ISO 2909
appearance	YELLOW		visuell
density at 15°C	849	kg/m ³	DIN EN ISO 12185
pour point	-45	°C	ASTM D 7346

JB GERMAN OIL GmbH & Co. KG · Wörlzower Weg 13-19 · D-19243 Wittenburg · Telefon +49 38852 90620 · Telefax +49 38852 906220

Note: All listed information complied with the latest knowledge and developments at the time of preparation. Our products will be continuously developed. For this reason, our products, manufacturing processes and all related information on this product page may change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under corresponding laboratory conditions and are to be regarded as general, non-binding guideline values.

Last Update: March 11, 2021