Product Information

JB GERMAN OIL Mineral Extra 15W-40

J2026

Description

JB GERMAN OIL Mineral Extra 15W-40 is a semi-synthetic high-performance, smooth-running engine oil for carburettor and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions. JB GERMAN OIL Mineral Extra 15W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. With JB GERMAN OIL Mineral Extra 15W-40, a reliable and heavy-duty engine oil has been developed.

Instructions for use

JB GERMAN OIL Mineral Extra 15W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. JB GERMAN OIL Mineral Extra 15W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SL/CF
- ACEA A3/B4

Recommendation

- Fiat 9.55535-D2/-G2
- MB 229.1
- VW 501 01/VW 505 00

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Excellent cold starting properties, even at low temperatures
- A very stable and excellent viscosity behavior and shear stability
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	95,5	mm^2/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	13,7	mm^2/s	DIN 51659-2:2017-02
Viscosity Index	144		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	868	kg/m^3	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.