Product Information

JB GERMAN OIL Excellence SAE 0W-30

J2031

Description

JB GERMAN OIL Excellence SAE 0W_30 is a synthetic Low-SAPS low-friction engine oil for passenger car diesel and gasoline engines. It is characterized by excellent cold-start characteristics, minimization of fuel consumption, friction and wear. JB GERMAN OIL Excellence SAE 0W_30 achieves a high viscosity index through its formulation with special base oils.

Instructions for use

JB GERMAN OIL Excellence SAE 0W_30 is ideally suited for energy-saving, year-round use in modern passenger car diesel and gasoline engines. It is used in engines of Ford with the specified specifications. The operating regulations of the motor vehicle and engine manufacturers must be observed.

Quality classification

Specification

- ACEA C2

Recommendation

- Fiat 9.55535-GS1/-DS1
- Ford WSS-M2C950-A
- Jaguar Land Rover STJLR.03.5007
- VWC 53035

Properties

- Fuel saving under all operating conditions
- Neutrality against sealing properties
- Extended oil exchange intervals protect natural resources
- Suitable for diesel particulate filters
- Excellent cold-start characteristics even at low temperatures below -30°C
- Low evaporation tendency and therefore low oil consumption
- Provides extensive protection against wear, corrosion and froth
- Low SAPS = reduced sulfate ash, phosphorus and sulfur

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	46,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9,8	mm²/s	DIN 51659-2:2017-02
Viscosity Index	206		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	846	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-45	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.