Product Information

JB GERMAN OIL Farmer Super SAE 30 Mineral 4 Takt

J2033

Description

JB GERMAN OIL Farmer Super SAE 30 Mineral 4 Takt is a mono-grade engine-oil. Selected base oils and additives ensure optimum lubrication and operational safety.

Instructions for use

JB GERMAN OIL Farmer Super SAE 30 Mineral 4 Takt is suitable for 4-stroke mowing machines. The operating instructions of the engine manufacturer must be observed.

Quality classification

Specification

- API SG/CF
- ACEA E2/B4

Properties

- Suitable for catalysts
- Prevention of the formation of black mud
- Stable and excellent viscosity behavior
- Neutrality against sealing materials
- Very good shear stability
- High oxidation stability
- Good detergents and dispersing properties
- Great protection against wear and corrosion

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	98,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	11,7	mm²/s	DIN 51659-2:2017-02
Viscosity Index	109		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	880,5	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.