Product Information

JB GERMAN OIL Longlife WIV SP Pro SAE 5W-30

J2047

Description

JB GERMAN OIL Longlife WIV SP Pro SAE 5W-30 is a synthetic low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Minimization of friction, wear and fuel consumption, excellent cold start properties. Extended oil change intervals according to the manufacturer's instructions. It extends the service life of the exhaust aftertreatment system by reducing the concentration of ash-forming particles in the exhaust gas. Reduces the release of harmful emissions into the environment. Offers more safety thanks to the high level of protection for the motors. Thanks to its formulation with special base oils, it has a high viscosity index.

Instructions for use

JB GERMAN OIL Longlife WIV SP Pro SAE 5W-30 is ideal for energy-saving year-round use in modern gasoline and diesel engines. It is suitable for extended oil change intervals and extends the service life of the xhaust aftertreatment system. It meets the technical requirements of OPEL OV0401547-G30 /-D30 and meets the requirements of GM dexos1 Gen2, which is a combination of parts from ILSAC GF-6, ACEA A5/B5 and GM engine tests. The operating regulations of the vehicle and engine manufacturers must be observed.

Quality classification

Specification

- API SP/SQ
- ACEA C3

Recommendation

- BMW Longlife-04
- Fiat 9.55535-S3
- MB 229.31
- MB 229.51
- MB 229.52
- VW 504 00/507 00
- GM dexos 2™
- GM dexos1™ Gen 2
- Opel/Vauxhall OV0401547-D30
- Opel/Vauxhall OV0401547-G30
- Porsche C30
- Renault RN17

Properties

- Fuel savings under all operating conditions
- Neutrality towards sealing materials
- Low evaporation tendency, thus lower oil consumption
- Catalyst suitability
- Extended oil change intervals protect natural resources
- Excellent cold start properties even at low temperatures of below -30 ° C
- Extremely stable and excellent viscosity behavior, shear stability
- Safe lubricating film at high operating temperatures
- Excellent protection against wear, corrosion and foam formation

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	75.9	mm^2/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12.4	mm^2/s	DIN 51659-2:2017-02
Viscosity Index	162		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	855	kg/m^3	DIN EN ISO 12185:1997-11
Pour Point	-42	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.