Product Information

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

J2048

Description

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30 is a synthetic Low SAPS smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol car engines. JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SP
- ACEA C2/C3

Recommendation

- BMW Longlife-04
- MB 229.31, MB 229.51, MB 229.52
- OV0401547-G30
- Renault RN17

Properties

- Fuel savings under all operating conditions
- A very stable and excellent viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Extensive protection against wear, corrosion and foaming
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources
- Excellent cold starting properties
- Low SAPS = low sulphated ash, phosphorous and sulphur

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	75.4	mm^2/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12.4	mm^2/s	DIN 51659-2:2017-02
Viscosity Index	163		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	852	kg/m^3	DIN EN ISO 12185:1997-11
Pour Point	-42	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.