Product Information

JB GERMAN OIL Truckstar 10W-40

J2058

Description

JB GERMAN OIL Truckstar 10W-40 is a high-quality lorry engine oil which is formulated with Low SAPS technology. It can be used in both older and newer engines. JB GERMAN OIL Truckstar 10W-40 improves the performance, reliability and cleanliness of engines. It reduces the fuel consumption and wear, as it reduces friction.

Instructions for use

JB GERMAN OIL Truckstar 10W-40 is a high-performance motor oil that can be used all year round. It was also designed for vehicles with exhaust gas recirculation systems in line with the new exhaust emission guidelines. JB GERMAN OIL Truckstar 10W-40 can be used universally in all diesel engines with and without turbocharging. Suitable for EURO I, II, III, IV, V and EURO VI engines.

Quality classification

Specification

- API CK-4/SN
- ACEA E6/E7/E8/E9/E11
- JASO DH-2

Recommendation

- Caterpillar ECF-1/ECF-2/ECF-3
- Cummins CES 20076/20077
- Cummins CES 20081/20086
- DAF HP-2
- DDC 93K218, DDC 93K222
- Deutz DQC IV-10 LA
- Iveco 18-1804 TLS E9
- Mack EOS-4.5
- MB 226.9
- DTFR 15C100 (228.31), DTFR 15C110 (228.51)
- MAN M 3477 / 3575 / 3275 / 3271-1
- MAN M 3775
- MTU Typ 3.1
- Renault Trucks RGD/RXD
- Renault VI RLD-3
- Scania Low Ash
- VOLVO VDS-4.5

Properties

- Stable viscosity behaviour
- Excellent detergent & dispersing properties
- High oxidation stability & engine cleanliness
- Protection against silting, coking & varnish
- Very good wear and corrosion protection

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	92.7	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14.2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	158		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	862	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.