Product Information

JB GERMAN OIL Truckstar EURO VI SAE 10W-40

J2063

Description

JB GERMAN OIL Truckstar EURO VI SAE 10W-40 is a smooth-running engine oil for all diesel engines with and without turbo charging in lorries, buses and machinery. It has an excellent flow behaviour, even at low temperatures. It quickly reaches critical lubrication points, thus ensuring a considerable reduction in wear during the warm-up phase. Selected active ingredients ensure maximum engine cleanliness, even in short-haul traffic. JB GERMAN OIL Truckstar EURO VI SAE 10W-40 allows for extended oil change intervals in accordance with manufacturer's instructions, and high wear protection with low oil and fuel consumption.

Instructions for use

JB GERMAN OIL Truckstar EURO VI SAE 10W-40 is ideal for mixed fleets. It can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API CI-4
- ACEA E4/E7
- Global DHD-1
- JASO DH-1

Recommendation

- Cummins CES 20076/20077/20078
- Daewoo-Avia
- DAF HP-1, DAF HP-2
- DDC 93K215
- Deutz DQC III-10
- DTFR 15B120 (228.5)
- Iveco 18-1804 T3 E4
- Mack EO-N
- MAN M 3277
- MTU Type 3
- Renault VI RLD-2
- Renault VI RXD
- SCANIA LDF-2
- Tatra TDS 40/16
- TEDOM 258-4
- Voith Retarder B
- Volvo VDS-3
- Zetor

Properties

- Reduction in fuel consumption due to smooth running characteristics
- Protection against formation of mirror surfaces on cylinder tracks
- Protection against corrosion, silting and bonding
- Fastest possible lubrication after starting
- Reduction of exhaust gas particles
- Environmental friendliness due to longest oil change intervals

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	103,8	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	15,3	mm²/s	DIN 51659-2:2017-02
Viscosity Index	155		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	866	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.