Product Information

JB GERMAN OIL Longlife DXS GM 5W-30

J2064

Description

JB GERMAN OIL Longlife DXS GM 5W-30 is a fully synthetic Mid SAPS smooth-running engine oil for petrol car engines with or without turbocharging and direct injection. JB GERMAN OIL Longlife DXS GM 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

JB GERMAN OIL Longlife DXS GM 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol car engines. According to dexos1™ Gen3 specification it is recommended for General Motors under all operating conditions. The operating instructions of the car and engine manufacturers must be observed.

Quality classification

Specification

- API SP
- API SQ (RC)
- ILSAC GF-5/GF-6A
- ILSAC GF-7A

Recommendation

- Chrysler MS-6395
- dexos1™ Gen3
- Fiat 9.55535-CR1
- Ford WSS-M2C929-A, Ford WSS-M2C946-A/-B1
- Ford WSS-M2C961-A
- GM 6094M
- Opel/Vauxhall OV0401547-G30
- VWC 53034

Properties

- A very stable and excellent viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Excellent protection against wear, corrosion and foaming
- High oxidation stability
- Excellent cold starting properties
- Fuel savings under all operating conditions
- Neutrality towards sealants
- Suitable for catalytic converters
- A secure lubricant film at very high operating temperatures

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	60,1	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	10,8	mm²/s	DIN 51659-2:2017-02
Viscosity Index	172		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	846	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.