Product Information

JB GERMAN OIL Scooter Young Power 4T 10W-40

J2066

Description

JB GERMAN OIL Scooter Young Power 4T 10W-40 is a engine oil for demanding 4-stroke motorbikes. It allows for fuel-saving engine operation and is specifically designed for wet and lubricated couplings. JB GERMAN OIL Scooter Young Power 4T 10W-40 is characterized by its excellent cold starting properties, as it ensures optimum lubrication reliability during the cold-running phase.

Instructions for use

JB GERMAN OIL Scooter Young Power 4T 10W-40 is especially suitable as a high-performance, smooth-running engine oil for all motorcycles, when the specification JASO MA2 T904:2006 SAE 10W-40 is required. JB GERMAN OIL Scooter Young Power 4T 10W-40 meets the high-tech demands of the latest high-performance engine generation. For professional racing we recommend our racing products.

Quality classification

Specification

- API SL
- JASO MA2

Recommendation

- Aprilia
- BMW
- Ducati
- Honda
- Kawasaki
- Moto-Guzzi
- Suzuki
- Triumph
- Yamaha

Properties

- Excellent cold starting properties
- Very good detergent and dispersing properties
- Low evaporation, thus low oil consumption
- Prevention of silting, varnish, coking and corrosion
- Very stable viscosity index
- Fast lubrication of the engine
- No oil-related deposits in combustion chambers, in piston ring zones and valves

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	97,7	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14,4	mm²/s	DIN 51659-2:2017-02
Viscosity Index	152		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	864	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.