Product Information

JB GERMAN OIL Dynamic TDI SAE 5W-40 PD

J2079

Description

JB GERMAN OIL Dynamic TDI SAE 5W-40 PD is a high-performance engine oil for modern petrol and diesel engines in passenger cars and vans. It is especially recommended for use in engines with turbocharger and multi-valve technology.

Instructions for use

JB GERMAN OIL Dynamic TDI SAE 5W-40 PD can be used as a year-round oil. It is suitable for short-haul and long-haul operation. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SN/CF
- ACEA C3

Recommendation

- BMW Longlife-04
- Chrysler MS-11106
- dexos2™
- Fiat 9.55535-S2
- Ford WSS-M2C917-A
- MB 226.5, MB 229.31, MB 229.51
- Porsche C40
- Renault RN0700/RN0710
- VW 502 00/505 00/505 01

Properties

- Excellent cold start properties
- High fuel economy
- Very high wear protection
- Excellent oxidation stability through the use of high quality base oils
- Safe lubrication even at high operating temperatures
- Suitable for use in petrol and diesel engines from different manufacturers

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	80,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	13,3	mm²/s	DIN 51659-2:2017-02
Viscosity Index	170		DIN ISO 2909:2004-08
Appearance	YELLOW BROWN		VISUELL
Density at 15°C	852	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.