Product Information

JB GERMAN OIL Lightrun 2000S SAE 10W-40

J2082

Description

JB GERMAN OIL Lightrun 2000S SAE 10W-40 is a high-quality smooth-running engine oil for year-round use in highly stressed aspirated and turbo diesel engines as well as petrol engines. It has an excellent flow behaviour, even at low temperatures. It quickly reaches critical lubrication points, thus ensuring a considerable reduction in wear during the warm-up phase. Selected active ingredients ensure maximum engine cleanliness, even in short-haul traffic. JB GERMAN OIL Lightrun 2000S SAE 10W-40 allows for extended oil change intervals in accordance with manufacturer's instructions, and high wear protection with low oil and fuel consumption.

Instructions for use

JB GERMAN OIL Lightrun 2000S SAE 10W-40 is ideal for mixed fleets and can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API CI-4/SL
- Global DHD-1
- JASO DH-1
- ACEA A3/B4
- ACEA E3/E5/E7

Recommendation

- Allison C-4
- Caterpillar ECF-2, Caterpillar TO-2
- Cummins CES 20076/20077/20078
- DAF
- DDC 93K215
- Deutz DQC III-10
- DTFR 15B110 (228.3), DTFR 13D110 (235.28)
- Mack EO-N
- MAN M 3275-1
- MB 229.1
- MTU Type 2
- Renault VI RLD-2
- Voith Retarder B
- Volvo VDS-3
- VW 500 00/501 01/505 00

Properties

- Very good detergent and dispersing properties
- Protection against reflective surface formation
- Extended oil change intervals protect natural resources
- High resistance to oxidation and ageing
- Good cold starting properties

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	99,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14,5	mm²/s	DIN 51659-2:2017-02
Viscosity Index	152		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	869	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.