Product Information

JB GERMAN OIL Longlife P5 SAE 5W-40

J2085

Description

JB GERMAN OIL Longlife P5 SAE 5W-40 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions. JB GERMAN OIL Longlife P5 SAE 5W-40 offers maximum operational safety in all driving conditions, for example in extreme stop-and-go traffic in big cities, as well as during high-speed motorway driving.

Instructions for use

JB GERMAN OIL Longlife P5 SAE 5W-40 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol and diesel car engines.

Quality classification

Specification

- API SP
- ACEA A3/B4

Recommendation

- BMW Longlife-01
- Chrysler MS-10725, Chrysler MS-12991
- Fiat 9.55535-H2/-M2
- MB 226.5, MB 229.3
- Opel GM LL-B-025
- Porsche A40
- PSA B71 2296
- Renault RN0700/RN0710
- VW 502 00/505 00

Properties

- Fuel savings under all operating conditions
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- Excellent cold starting properties, even at low temperatures
- Very good detergent and dispersing properties
- Extensive protection against wear, corrosion and foaming

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	78,1	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	13,3	mm²/s	DIN 51659-2:2017-02
Viscosity Index	174		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	850	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.