Product Information

JB GERMAN OIL LL-Spezial FO SAE 5W-30

J2090

Description

JB GERMAN OIL LL-Spezial FO SAE 5W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions. JB GERMAN OIL LL-Spezial FO SAE 5W-30 is an engine oil specifically for the requirements of Ford and Renault.

Instructions for use

JB GERMAN OIL LL-Spezial FO SAE 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol and diesel car engines. It can be used in Ford and Renault engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SL
- ACEA A5/B5

Recommendation

- Ford WSS-M2C913-A/-B/-C/-D
- Renault RN0700
- VWC 53036

Properties

- Fuel savings under all operating conditions
- Excellent cold starting properties, even at low temperatures
- Neutrality towards sealants
- Very good detergent and dispersing properties
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	56.4	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	10.0	mm²/s	DIN 51659-2:2017-02
Viscosity Index	165		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	852	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.