Product Information

JB GERMAN OIL Longlife ASIA C3 SAE 5W-30

J2092

Description

JB GERMAN OIL Longlife ASIA C3 SAE 5W-30 is a synthetic low SAPS light-running engine oil for petrol and diesel engines with and without turbocharging and direct injection, which was specially designed for vehicles of the Asian automobile manufacturers. It is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. In order to guarantee the low viscosity of the SAPS class 5W and at the same time a low evaporation loss, was with JB GERMAN OIL Longlife ASIA C3 SAE 5W-30 developed a reliable and heavy-duty engine oil. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

JB GERMAN OIL Longlife ASIA C3 SAE 5W-30 is ideally suited for energy-saving year-round use in all modern petrol and diesel engines. It is used in engines with the specified specifications. The operating regulations of the motor vehicle and engine manufacturers are to be observed.

Quality classification

Specification

- API SN/CF
- ACEA C3

Recommendation

- Brilliance
- BYD
- Chery
- Daihatsu
- Honda
- Hyundai
- Kia
- Mazda
- Mitsubishi
- Nissan
- Subaru
- Suzuki
- Toyota

Properties

- Fuel saving under all operating conditions
- Neutrality to sealing materials
- Catalyst suitability
- Low evaporation tendency, thus low oil consumption
- Extended oil change intervals protect natural resources
- A very stable and excellent viscosity behavior, shear stability
- Very good detergent and dispersing properties
- An extensive protection against wear, corrosion and foaming
- Very good cold-start properties
- Low SAPS = Low sulphate ash, phosphorus and sulfur content

Technical specifications

Properties	Data	Unit	Testing under
Kinematic viscosity at 40°C	73,5	mm²/s	DIN ISO 51562-2:1988-12
Kinematic viscosity at 100°C	12	mm²/s	DIN ISO 51562-2:1988-12
Viscosity index	166		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	852	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-35	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.