Product Information

JB GERMAN OIL Super Semi Synth. SAE 10W-30

J2093

Description

JB GERMAN OIL Super Semi Synth. SAE 10W-30 is a synthetic high-performance, low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Extended oil change intervals according to the manufacturer's instructions. It is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. With JB GERMAN OIL Super Semi Synth. SAE 10W-30, a reliable and heavy-duty engine oil has been developed.

Instructions for use

JB GERMAN OIL Super Semi Synth. SAE 10W-30 is ideally suited for year-round use in all modern passenger cars with gasoline and diesel engines. It is used in engines with the specified specifications. The operating regulations of the vehicle and engine manufacturers must be observed.

Quality classification

Specification

- API SN/CF
- ACEA A3/B4

Recommendation

- MB 229.1

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersant properties
- Neutrality towards sealing materials
- Low evaporation tendency, thus lower oil consumption
- Catalyst suitability
- Excellent cold start properties even at low temperatures of below -25 ° C
- Very stable and excellent viscosity behavior, shear stability
- Extensive protection against wear, corrosion and foam formation
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	81,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12,2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	146		DIN ISO 2909:2004-08
Appearance	REDBROWN		VISUELL
Density at 15°C	863	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.