Product Information

JB GERMAN OIL ATF DEXRON II D

J2266

Description

JB GERMAN OIL ATF DEXRON II D is a very high-quality gear fluid for automatic gearboxes of all vehicles and machinery. It is made with a base of highly refined mineral oils with suitable additives. It was developed especially for the indicated specifications and purposes. JB GERMAN OIL ATF DEXRON II D provides maximum lubrication and wear protection thanks to its special additives.

Instructions for use

JB GERMAN OIL ATF DEXRON II D was developed for use in automatic gearboxes, hydraulic steering systems, converters and power transmissions, and can be used as a universal ATF (automatic transmission fluid) for all vehicles and machinery. It is recommended if an ATF type Dexron D II must be used in accordance with the manufacturer's specifications. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- GM Dexron® II D
- Ford MERCON®

Recommendation

- Caterpillar TO-2
- Ford ESP-M2C166-H, Ford WSS-M2C185-A
- Ford SQM-2C9010-B, Ford WSS-M2C138-CJ
- MAN 339 Typ Z1
- DTFR 13C120 (236.2), MB 236.6
- DTFR 13C140 (236.7)
- Renk Doromat
- VOITH 55.6335.xx
- ZF TE-ML 03D/04D/11A/14A/17C/05L

Properties

- Stable and excellent viscosity-temperature behavior
- Problem-free, both at very low and very high temperatures
- Extremely high thermal load bearing capacity
- Neutral towards sealing agents
- Reliable protection against wear, silting, bonding and corrosion
- Foam-free, even under the heaviest of loads
- Miscibility and compatibility with all brands of ATFs

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	35,0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	176		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	848	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-54	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.