Product Information

JB GERMAN OIL ATF DQ 8001 Fluid RED

J2377

Description

JB GERMAN OIL ATF DQ 8001 Fluid RED is designed on a basis of hydrocrack oils and PAO with special additives and inhibition, which guarantee the flawless function of the automatic gearbox. JB GERMAN OIL ATF DQ 8001 Fluid RED is an ATF of the latest generation for all 8-gear automatic gearboxes and some 6-gear automatic gearboxes from ZF. A high wear protection is guaranteed in all operating conditions.

Instructions for use

JB GERMAN OIL ATF DQ 8001 Fluid RED was developed for use in the new 8HP series gearboxes of ZF 8HP45, 8HP55, 8HP70, 8HP90, as well as for the 6-gear machines of the 6HP series - 6HP19X for AUDI Q7, 6HP19A and 6HP28AF. Observance of the manufacturers' original part numbers.

Quality classification

Specification

- Aisin Warner AW-1
- JASO 1A LV

Recommendation

- Audi G 055 005, Audi G 055 162, Audi G 052 540
- BMW 83 22 0 142 516, BMW 83 22 2 152 426
- DSIH 6p805 (Geely, Ssangyong,Mahindra 6sp)
- Honda DW-1
- Hyundai/Kia NWS 9638 T-5
- Hyundai/Kia SP-IV/SPH-IV/SP-IV RR
- MB 236.12, MB 236.14, MB 236.41
- Mitsubishi ATF-J3/ATF-PA, Mitsubishi SP-IV
- Nissan Matic-S, Nissan Matic-W
- Saab 93 165 147
- Toyota WS (JWS 3324)
- Volvo 6 speed MY2011-2013 (P/N 31256675)
- Volvo 6 speed MY2011-2013 (P/N 31256774)
- VW G 052 540, VW G 055 005, VW G 055 162
- VW G 055 540 A2, VW G 060 162
- ZF Lifeguard Fluid 8

Properties

- High and stable viscosity index
- Very good oxidation stability
- High thermal and oxidative stability
- Excellent cooling capacity
- Reliable protection against wear, corrosion and foaming
- Good lubrication properties, even at low temperatures in winter
- Coordinated friction properties

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	24.8	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	5,5	mm²/s	DIN 51659-2:2017-02
Viscosity Index	169		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	842	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.