Product Information

JB GERMAN OIL Eco Longlife III SAE 5W-30

J2418

Description

JB GERMAN OIL Eco Longlife III SAE 5W-30 is a synthetic smooth-running engine oil for modern petrol and diesel car engines with or without turbocharging and direct-injection. JB GERMAN OIL Eco Longlife III SAE 5W-30 is characterized by its minimization of fuel consumption, an excellent oil supply during cold starting and ensures a high level of wear and corrosion prevention. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

JB GERMAN OIL Eco Longlife III SAE 5W-30 is an energy-efficient engine oil for year-round use and ideal for all modern petrol and diesel car engines. JB GERMAN OIL Eco Longlife III SAE 5W-30 extends the services life of the diesel particulate filter. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SN
- ACEA C3

Recommendation

- BMW Longlife-04
- Fiat 9.55535-S3
- MB 229.31, MB 229.51
- Porsche C30
- Renault RN17
- VW 504 00/507 00

Properties

- Excellent cold starting properties
- High shear stability
- Neutrality towards sealants
- Suitable for catalytic converters
- A very stable and excellent viscosity behavior, even at high speeds
- Fuel savings under all operating conditions
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	73,2	mm^2/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12,2	mm^2/s	DIN 51659-2:2017-02
Viscosity Index	164		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	849	kg/m^3	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.