Product Information

JB GERMAN OIL CLP 460

J3353

Description

JB GERMAN OIL CLP 460 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, high-pressure capacity under impact loads. Due to the low pour point of JB GERMAN OIL CLP 460, the cold behavior of this product is excellent.

Instructions for use

JB GERMAN OIL CLP 460 has very good properties as a lubricant. JB GERMAN OIL CLP 460 can therefore be used in largely all industrial areas under stress and impact loads.

Quality classification

Specification

- AGMA 9005-D94
- DIN 51517-3

Recommendation

- Cincinnati Milacron
- Clean Panel Coker
- US Steel 224
- US Steel S-200

Properties

- A low pour point
- An excellent wear protection
- Prevents foam formation
- Zinc free
- A stable, high-pressure capacity under impact loads
- An excellent cold behavior
- Inhibits rust and corrosion

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	469.3	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	30.9	mm²/s	DIN 51659-2:2017-02
Viscosity Index	103		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	899	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-12	°C	ASTM D 7346:2015

JB German Oil GmbH | Wölzower Weg 13 - 19 | D-19243 Wittenburg | Telefon: +49 (0) 38852 90620 | Telefax: +49 (0) 38852 906220

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.