JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier

Trade name/designation:

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

Article No.:
J2048

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:
Lubricant

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

JB German Oil GmbH
Wölzower Weg 13 – 19
19243 Wittenburg
Germany
Telephone: +49 (0) 38852 90620
Telefax: +49 (0) 38852 906220
E-mail: Vertrieb@jb-germanoil.de
Website: www.jb-germanoil.de

E-mail (competent person): vertrieb@jb-germanoil.de

1.4. Emergency telephone number

Abt. Produktsicherheit, 24h: +49 228 192 40 (Informationszentrale gegen Vergiftungen Bonn), +49 (0) 38852 90620 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

According to EC directives or the corresponding national regulations the product does not have to be labelled.

Hazard statements: none
Supplemental hazard information: none
Precautionary statements: none

2.3. Other hazards

No data available

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-54-7 EC No.: 265-157-1 REACH No.: 01-2119484627-25	**Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified** Asp. Tox. 1 (H304) Danger **Acute Toxicity Estimate** ATE (oral) 5,000 mg/kg ATE (dermal) 5,000 mg/kg ATE (inhalation, dust/mist) 5.53 mg/L	28 – ≤ 50 weight-%
CAS No.: 70024-69-0 EC No.: 274-263-7 REACH No.: 01-2119492616-28	**Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts** Skin Sens. 1B (H317) Warning **Specific concentration limit (SCL)** Skin Sens. 1B; H317: 10% ≤ C < 100% **Acute Toxicity Estimate** ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg	0 – ≤ 1 weight-%
CAS No.: 68411-46-1 EC No.: 270-128-1 REACH No.: 01-2119491299-23	**Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene** Repr. 2 (H361) Warning **Acute Toxicity Estimate** ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) ≥ 5 mg/L	0 – < 0.44 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:
Provide fresh air. Consult a doctor immediately.

In case of skin contact:
After contact with skin, wash immediately with plenty of water and soap. Consult a doctor immediately.

After eye contact:
In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:
Rinse mouth thoroughly with water. Do NOT induce vomiting. Consult a doctor immediately. Rinse mouth. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

Self-protection of the first aider:
First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Observe risk of aspiration if vomiting occurs.

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
Use water spray jet to protect personnel and to cool endangered containers.

Unsuitable extinguishing media:
Full water jet

5.2. Special hazards arising from the substance or mixture

During heating or in case of fire, toxic gases is possible.
The formation of combustible vapours is possible at temperatures above: Flash point

Hazardous combustion products:
Carbon monoxide, Carbon dioxide (CO2), Nitrogen oxides (NOx),
During heating or in case of fire, toxic gases is possible. In case of fire: Gases/vapours, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:
Use personal protection equipment. Special danger of slipping by leaking/spilling product. Avoid breathing dust/fume/gas/mist/vapours/spray. Remove persons to safety.

Protective equipment:
Wear protective gloves/protective clothing/eye protection/face protection.

Emergency procedures:
Remove persons to safety.

6.1.2. For emergency responders

Personal protection equipment:
Use personal protection equipment. Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:
Suitable material for taking up: Sand, Kieselguhr, Universal binder, Chemical binding agents, containing acids

For cleaning up:
Remove from the water surface (e.g. skimming, sucking). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information:
Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

6.5. Additional information
Clear spills immediately. Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:
Personal protection equipment: see section 8 When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Clear spills immediately. Use appropriate container to avoid environmental contamination. Wear personal protection equipment (refer to section 8).

Fire prevent measures:
No special fire protection measures are necessary.

Environmental precautions:
See section 8.

Advices on general occupational hygiene
Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:
Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:
Suitable container/equipment material: Floors should be impervious, resistant to liquids and easy to clean. Shafts and sewers must be protected from entry of the product.
Keep/Store only in original container.

Hints on storage assembly:
not required

Storage class (TRGS 510, Germany): 10 – Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:
Store in a cool dry place. Keep away from heat.

7.3. Specific end use(s)

Recommendation:
Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE) from 29 Mar 2019	**diphenylamine** CAS No.: 122-39-4 EC No.: 204-539-4	① 5 mg/m³ ② 10 mg/m³ ⑤ (kann über die Haut aufgenommen werden) DFG, Y, H

8.1.2. Biological limit values
No data available

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	11.75 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	3.33 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	4.37 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	1.09 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.62 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.31 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.31 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
Distillates (petroleum), solvent-refined heavy paraffinic CAS No.: 64741-88-4 EC No.: 265-090-8	9.33 mg/kg	① PNEC secondary poisoning
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	1 mg/L	① PNEC aquatic, freshwater
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	1 mg/L	① PNEC aquatic, marine water
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	1,000 mg/L	① PNEC sewage treatment plant
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	16.667 mg/kg bw/day	① PNEC secondary poisoning
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	10 mg/L	① PNEC aquatic, intermittent release
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.0338 mg/L	① PNEC aquatic, freshwater

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

Substance name	PNEC Value	① PNEC type
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.0038 mg/L	① PNEC aquatic, marine water
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	10 mg/L	① PNEC sewage treatment plant
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.446 mg/kg	① PNEC sediment, freshwater
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.0446 mg/kg	① PNEC sediment, marine water
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	2.59 mg/kg	① PNEC soil
Distillates (petroleum), solvent-dewaxed heavy paraffinic CAS No.: 64742-65-0 EC No.: 265-169-7	9.33 mg/kg	① PNEC secondary poisoning

8.2. Exposure controls

8.2.1. Appropriate engineering controls

See section 7. No additional measures necessary.

8.2.2. Personal protection equipment

Eye/face protection:

During transfer: Eye glasses with side protection
Wear eye/face protection. EN 166

Skin protection:

Hand protection
Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), CR (polychloroprene, chloroprene rubber)
Thickness of the glove material: ≥ 0,4 mm
Breakthrough time: 480 min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
Tested protective gloves must be worn: EN ISO 374

Suitable protective clothing: Protective clothing In the case of wanting to use the gloves again, clean them before taking off and air them well.

Respiratory protection:

Usually no personal respirative protection necessary.

8.2.3. Environmental exposure controls

See section 7. No additional measures necessary.

8.3. Additional information

Mineral oil mist limits:
OSHA PEL - value 5 mg / m³, ACGIH STEL - value of 10 mg / m³

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid
Colour: light yellow
Odour: not determined
flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	*No data available*		
Melting point	*No data available*		
Freezing point	-42 °C		
Initial boiling point and boiling range	*No data available*		
Flash point	232 °C		
Evaporation rate	*No data available*		
Auto-ignition temperature	*No data available*		
Upper/lower flammability or explosive limits	*No data available*		
Vapour pressure	*No data available*		
Vapour density	*No data available*		
Density	852 kg/m³	15 °C	
Bulk density	*not applicable*		
Water solubility	*No data available*		
Dynamic viscosity	*No data available*		
Kinematic viscosity	75 mm²/s	40 °C	

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

To avoid thermal decomposition do not overheat.

10.5. Incompatible materials

Materials to avoid: Acid, Oxidising agent, Reducing agent

10.6. Hazardous decomposition products

Hazardous combustion products: Carbon dioxide, Carbon monoxide, Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified CAS No.: 64742-54-7 EC No.: 265-157-1
LD_{50} oral: 5,000 mg/kg (Rat) OECD 401
LD_{50} dermal: 5,000 mg/kg (Rabbit) OECD 402
LC_{50} Acute inhalation toxicity (dust/mist): 5.53 mg/L 4 h (Rat) OECD 403

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7	
LD_{50} oral: >5,000 mg/kg (Rat)	
LD_{50} dermal: >2,000 mg/kg (Rabbit)	
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	
LD_{50} oral: >5,000 mg/kg (rat)	
LD_{50} dermal: >2,000 mg/kg (Rat) OECD-402	
LC_{50} Acute inhalation toxicity (dust/mist): ≥5 mg/L	

Acute oral toxicity:
Based on available data, the classification criteria are not met.

Acute dermal toxicity:
Based on available data, the classification criteria are not met.

Acute inhalation toxicity:
Based on available data, the classification criteria are not met.

Skin corrosion/irritation:
Based on available data, the classification criteria are not met.

Serious eye damage/irritation:
Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:
Based on available data, the classification criteria are not met.

Germ cell mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity:
Based on available data, the classification criteria are not met.

STOT-single exposure:
Based on available data, the classification criteria are not met.

STOT-repeated exposure:
Based on available data, the classification criteria are not met.

Aspiration hazard:
Based on available data, the classification criteria are not met.

Additional information:
No data available

11.2. Information on other hazards

Endocrine disrupting properties:
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified CAS No.: 64742-54-7 EC No.: 265-157-1	
LC_{50}: 100 mg/L 4 d (fish)	
LC_{50}: 10,000 mg/L 4 d (crustaceans)	
EC_{50}: 10,000 mg/L 2 d (crustaceans)	
NOEC: 100 mg/L 4 d (fish)	
NOEC: 100 mg/L 3 d (Algae/water plant)	
NOEC: ≥100 mg/L 3 d (Algae/water plant, Algen)	

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7
LC_{50}: >1,000 mg/L 4 d (fish)
EC_{50}: >1,000 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
ErC_{50}: >1,000 mg/L 3 d (Algae/water plant)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1
LC_{50}: 100 mg/L 4 d (fish)
LC_{50}: >100 mg/L 4 d (fish, Danio rerio (previous name: Brachydanio rerio)) OECD Guideline 203 (Fish, Acute Toxicity Test)
EC_{50}: 51 mg/L 2 d (crustaceans)
EC_{50}: 100 mg/L 3 d (Algae/water plant)
EC_{50}: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)) OECD Guideline 201 (Alga, Growth Inhibition Test)
EC_{50}: 51 mg/L 2 d (crustaceans, Daphnia magna)
NOEC: 10 mg/L 2 d (crustaceans)
NOEC: ≥10 – ≤100 mg/L 3 d (Algae/water plant)
NOEC: 10 – 100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)) OECD Guideline 201 (Alga, Growth Inhibition Test)
NOEC: 10 mg/L 2 d (crustaceans, Daphnia magna)

12.2. Persistence and degradability
No data available

12.3. Bioaccumulative potential

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7
Log K_{OW}: 22.12
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1
Log K_{OW}: 6.66
Bioconcentration factor (BCF): 12,500

12.4. Mobility in soil
No data available

12.5. Results of PBT and vPvB assessment

Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified CAS No.: 64742-54-7 EC No.: 265-157-1
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts CAS No.: 70024-69-0 EC No.: 274-263-7
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties
This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects
No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Dispose of waste according to applicable legislation.

JB GERMAN OIL RS Hightec Synt SP Pro SAE 5W-30

Waste treatment options

Appropriate disposal / Product:
Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:
Non-contaminated packages may be recycled.

13.2. Additional information
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es)			
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental hazards			
not relevant	not relevant	not relevant	not relevant
14.6. Special precautions for user			
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):
This product is not assigned to a hazard category.
Safety data sheet available for professional user on request.

15.1.2. National regulations

[DE] National regulations

Störfallverordnung (12. BImschV)

for substances contained in the product:
This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:
To follow: 5.2.5

Water hazard class

WGK:
2 - obviously hazardous to water

Source:
Self-classification (mixture; calculation rule).

Technische Regeln für Gefahrstoffe
TRGS 510
Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)
Berufsgenossenschaftliche Informationen (DGUV-Informationen) 868
Berufsgenossenschaftliche Regeln (DGUV-Regeln) 189, 190, 192, 195

Other regulations, restrictions and prohibition regulations
Altöl-Verordnung (AltölV)

15.2. Chemical Safety Assessment
Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1. Indication of changes
No data available

16.2. Abbreviations and acronyms
See overview table at www.euphrac.eu
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data
EC 1907/2006 - REACH Regulation
1272/2008 EC - Regulation on classification, labeling and packaging of substances and mixtures, and amending Directives 67/548/EEC and 1999/45/EC and Regulation (EC) No 1907/2006
Regulation (EC) No 1907/2006 (REACH), Annex II
European Chemicals Agency (ECHA), C & L classification and labeling inventory
European Chemicals Agency (ECHA), ECHA CHEM Registered substances
OECD The Global Portal to Information on Chemical Substances (ChemPortal)
Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA): GESTIS substance database and International limit values for chemical substances
Federal Environment Agency, Section IV 2.4: Documentation and Information Centre substances hazardous to water Rigoletto (catalog substances hazardous to water)

Substance name	Type	source of supply
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	Classification of the substance or mixture; LC_{50}; EC_{50}; NOEC	Source: European Chemicals Agency, http://echa.europa.eu/

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]
The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility or the unborn child.

16.6. Training advice
No data available

16.7. Additional information
The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the

case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.